

A0020A Laser Linewidth Measurement System

SYCATUS Corporation

Laser linewidth measurement down to 40 kHz
Wide wavelength range of both C and L band
Interferometer and optical receiver in one box
Essential measurement for lasers for digital coherent systems

SYCATUS provides A0020A laser linewidth measurement system. A0020A achieves minimum linewidth measurement down to 40 kHz. A0020A operates in wide wavelength range of both C and L band.

Laser linewidth characteristics is the most critical item for laser diodes used in digital coherent transmission systems because of the narrow linewidth requirements for multilevel optical transmission.

Highly integrated optical source like ITLA also needs linewidth measurement to investigate the effect of the noise caused by electronics for laser conditioning.

A0020A enables the accurate characterization of laser diodes, which improves the performance and the quality of laser diodes. A0020A also reduces the measurement time and accelerate the development and the manufacturing of products.





Fig. 1 A0020A System Configuration

SYCATUS A0020A Laser Linewidth Measurement System

SYCATUS A0020A laser linewidth measurement system consists of SYCATUS laser linewidth test set and Keysight X-series signal analyzer.

The laser linewidth test set contains a delayed self-heterodyne interferometer followed by a high-gain linear optical receiver. The interferometer includes a polarization controller to adjust the interference condition.

By the combination of Keysight X-series signal analyzer, linewidth measured at 3 dB, 10 dB and 20 dB bandwidth can be obtained easily and immediately.



A0020A Laser Linewidth Measurement System




Fig. 2 Linewidth Measurement Example



SYCATUS Corporation

9-1, Takakuramachi, Hachioji,
Tokyo 192-0033, Japan

TEL : +81-42-660-0881
 FAX : +81-42-660-0882
 Email : inquiry@sycatus.com
 URL : www.sycatus.com/en

Specifications

Items	Specification
Optical Wavelength Range	1520 - 1620 nm, 1260 - 1360 nm or 1260 - 1620 nm
Minimum Linewidth Frequency	40 kHz or 10 kHz
Input Optical Power Range	-20 dBm to +7 dBm
Delay Fiber Length of Interferometer	5 km or 20 km
Frequency Shift of Interferometer	100 MHz

Ordering Information

Keysight Technologies

X-Series Signal Analyzer	N9000B CXA
	N9010B EXA
	N9020B MXA
	N9030B PXA

SYCATUS

Delayed Self-Heterodyne Interferometer	A0020A-DHI
Optical Receiver Built-In	A0020A-ORX
O-Band Addition, 1265-1365nm	A0020A-AOB
Delay Fiber Extension to 20 km	A0020A-D20



绿测科技有限公司

广州总部：广州市番禺区陈边村金欧大道83号江潮创意园A栋208室
 深圳分公司：深圳市龙华区龙华街道 油松社区东环一路1号耀丰通工业园1-2栋2栋607
 南宁分公司：广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号
 广州分公司：广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房
 电话：020-2204 2442
 传真：020-8067 2851
 邮箱：Sales@greentest.com.cn
 官网：www.greentest.com.cn



微信视频号



绿测科技订阅号



绿测工场服务号