

MODELS 9100/9200

300Vp-p Single / Dual Channel Signal Amplifiers



- High voltage output to 300Vp-p ($\pm 150V$)
- Output current to 150mA (9200: 100mA per channel)
- Full power bandwidth from DC to $>500kHz$
- Slew rate to $200V/\mu s$
- Low distortion
- Low cost
- Custom Configuration of:
 - Gain
 - Signal Ground

Model 9100/9200 is a Single/Dual Channel, 2U, half-rack size, bench-top power amplifier designed for signal amplification. With unprecedented signal purity, Model 9100/9200 amplifies signals from DC to over 500kHz. The unit has a fixed gain of x15 however the same amplifier is available with custom gain and no signal purity or performance degradation whatsoever.

Solves Common Problems

Model 9100/9200 operates as an amplifying buffer for signals emitted from waveform, function, or pulse generators. Most of these generators produce signals limited to 20Vp-p into high impedance. Model 9100/9200 can convert these voltages to levels as high as 300Vp-p. The amplifier has a current driving capability of $\pm 150mA$ (9200: $\pm 100mA$ per channel) from a 0.1W source. While the output can drive small capacitive or inductive loads, for full high speed potential it is recommended that the load characteristics should be mainly resistive. Model 9100/9200 can withstand load capacitance and inductance up to 100pF and 0.5mH without any performance deterioration

Ground Level

The advanced power amplifier is supplied with floating input and output connectors allowing flotation from ground level up to 250VDC. The only limitation is that both the input and output grounds must connect to the same level. This capability is extremely important in applications where the amplifying device must reside on the same ground level as its source. The floating capability can be added or removed using a simple, user-accessible, jumper connection.

Target Applications

The amplifier case was designed to stack on top or below other Tabor products. It can also be mounted alongside a Tabor generator in a standard 19" rack. The waveform-amplifier combo is an ideal solution for virtually any high-voltage, wide bandwidth application.

Cost Effective Solution

Model 9100/9200 power amplifier is yet another of Tabor's cost-effective solutions for a full range of high voltage applications.

MODELS 9100/9200

300Vp-p Single / Dual Channel Signal Amplifiers

Specification

CONFIGURATION

Channels:	
9100	1 single-ended output
9200	2 single-ended outputs

INPUT CHARACTERISTICS

No. of channels:	1/2
Connector:	Front panel BNCs
Impedance:	1M Ω , DC coupled
Damage Level:	50Vp-p
Frequency Range:	DC to 500kHz

OUTPUT CHARACTERISTICS

GENERAL

Connector:	Front panel BNCs
Impedance:	0.1 Ω , DC coupled
Protection:	Short-circuit, 10 seconds
Gain:	x15 ⁽²⁾ , fixed
Polarity:	Normal
Amplitude:	0 to 300Vp-p (\pm 150V)
Max. Output Current:	
9100	150mA
9200	100mA

SQUARE WAVE CHARACTERISTICS

Transition Time:	< 1.5 μ s
Aberrations:	< 15%

SINE WAVE CHARACTERISTICS

Bandwidth:	-3dB
Small Signal	1MHz, at 20Vp-p
Large Signal	500kHz, at 300Vp-p
Accuracy:	\pm (2% of full-scale amplitude range + 25mV), Square wave at 1kHz

THD:	
10Hz to 10kHz	< 0.1%
10kHz to 200kHz	< 1.2%,

GENERAL

Voltage Range:	100V/115V/230V
Frequency Range:	47Hz to 63Hz
Power Consumption:	60W
Signal Ground:	Floated to the same level as the source, 250VDC max.

Dimensions:	
With Feet	315 x 102 x 395 mm (WxHxD)
Without Feet	315 x 88 x 395 mm (WxHxD)

Weight:	
Without Package	6kg
Shipping Weight	7kg

Temperature:	
Operating	0°C to 50°C
Storage	-40°C to 70°C

Humidity: 80% RH, non condensing

Safety: CE Marked, IEC61010-1

Calibration: 1 years

Warranty^(*): 3 years standard

ORDERING INFORMATION

MODEL	DESCRIPTION
9100-15-G ⁽¹⁾	300Vp-p Single Channel Signal Amplifier
9200-15-G ⁽¹⁾	300Vp-p Dual Channel Signal Amplifier
Gain:	10 through 20, fixed ⁽²⁾
Signal Ground:	G = Tied to Ground; F = Floated Ground

⁽¹⁾ Standard Configuration

⁽²⁾ Custom gain from x10 to x20 can be ordered however, bandwidth cannot be maintained. Consult the factory before ordering gain above 15.

⁽³⁾ Specification is given for the standard configuration only



绿测科技有限公司

广州总部：广州市番禺区陈边村金欧大道83号江潮创意园A栋208室
 深圳分公司：深圳市龙华区龙华街道 油松社区东环一路1号耀丰通工业园1-2栋2栋607
 南宁分公司：广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号
 广州分公司：广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房
 电话：020-2204 2442
 传真：020-8067 2851
 邮箱：Sales@greentest.com.cn
 官网：www.greentest.com.cn



微信视频号



绿测科技订阅号



绿测工场服务号