

**NGX1000
PROGRAMMABLE
NOISE GENERATOR**

The Boonton NGX1000 programmable noise generator is a high performance, broadband additive white gaussian noise (AWGN) generator in an easy-to-use compact form factor. The streamlined user interface and flat menu structure provides a fast, simple way to add RF noise in a communications system to test reliability, robustness and performance. All functionality of the generator is accessible through the 5" touch screen or via remote control through an ethernet connection delivering flexible, programmable noise generation for broad use in semiconductor, military, aerospace, satellite, medical and communications applications. The NGX1000 is capable of generating noise in the frequency range of 10 MHz to 3 GHz with exceptional flatness over the entire frequency band and user-selectable attenuation from 0 dB to 127.9 dB in 0.1 dB steps. The noise output is through an N connector for fast, direct connection to a device or system under test.

FEATURES

- White Gaussian noise output
- Output power up to +10 dBm
- 127 dB of attenuation; 0.1 dB step size
- 5" touch screen display
- Noise output through female N connector
- Ethernet connection for remote control

NGX1000 Programmable Noise Generator

SPECIFICATIONS

Model	Frequency Range	Output Power	dBm / Hz	Flatness	$\mu\text{V} / \text{root Hz}$	Noise Attenuation
NGX1108B	10 MHz - 500 MHz	+10 dBm	-77 dBm	± 1.0 dBm	31.6	0 - 127.9 dB, 0.1 dB steps
NGX1110B	10 MHz - 1.5 GHz	+10 dBm	-82 dBm	± 1.5 dBm	18.2	0 - 127.9 dB, 0.1 dB steps
NGX1111B	1 GHz - 2 GHz	+10 dBm	-80 dBm	± 1.5 dBm	22.4	0 - 127.9 dB, 0.1 dB steps
NGX1112B	10 MHz - 2 GHz	0 dBm	-93 dBm	± 2.0 dBm	5.01	0 - 127.9 dB, 0.1 dB steps
NGX1113B	10 MHz - 3 GHz	0 dBm	-95 dBm	± 2.5 dBm	5.01	0 - 127.9 dB, 0.1 dB steps

- Noise attenuator accuracy:
 - ± 0.2 dB or 0.5% at 1 – 500 MHz
 - ± 0.2 dB or 1% at 0.5 – 1.0 GHz
 - ± 0.3 dB or 2% at 1 – 2 GHz
- Noise output through female N connector
- Ethernet connection for remote control
- 5" touch screen display
- Dimensions (HWD) – 3.5 in x 8.3 in x 11.2 in

OPTIONAL ACCESSORIES

- NGX1K-RMK Full-width 19" Rack Mount Kit (includes handles & hardware for mounting one or two generators)
- NGX1K-TCASE Transit case



绿测科技有限公司

广州总部：广州市番禺区陈边村金欧大道83号江潮创意园A栋208室
深圳分公司：深圳市龙华区龙华街道 油松社区东环一路1号耀丰通工业园1-2栋2栋607
南宁分公司：广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号
广州分公司：广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房
电话：020-2204 2442
传真：020-8067 2851
邮箱：Sales@greentest.com.cn
官网：www.greentest.com.cn



微信视频号



绿测科技订阅号



绿测工场服务号