

Technical data ProSim SPOT Light

Featuring an exclusive ergonomic design, the Pro-Sim SPOT Light is the first comprehensive SpO₂ functional tester to come in a handheld easy-touse device. SPOT Light is lightweight and flexible, with three custom presets specially-designed to make it the fastest and easiest-to-use device on the market today for pulse oximeter functional testing. A helpful LCD display and three simple buttons make it effortless to rapidly change parameters and view each signal output sent to the pulse oximeter at a glance. An interchangeable, long-life battery ensures uninterrupted all-day operation without the need to connect to a power supply.

SPOT Light sets up in seconds to send SpO₂ saturation, heart rate, perfusion, transmission, artifact noise, and eight different manufacturers custom R-curves to a pulse oximeter or patient monitor. It is designed to take the abuse of everyday use, including the stress of transportation, moving from room to room and device to device, and the occasional fall from the workbench.

An increasing number of medical devices now have pulse oximetry built in. SPOT Light can be paired with other Fluke Biomedical test tools to make modern device testing task fast and easy. Need to check a defibrillator with pulse oximetry? SPOT Light with the Impulse 7000 Defibrillator Analyzer allow you to test any external defibrillator on the market today. Do you have a fleet of new patient monitors coming that require incoming inspection? Using SPOT Light with ProSim 4 Vital Signs Simulator enables you to easily accomplish this task in hours instead of days.



Key features

- Small, portable, and lightweight, weighing in at 8.8 oz
- Large, easy to read LCD display
- Rechargeable battery lasts 10 hours minimum
- Signal strength indicator
- SpO₂ Saturation 70% to 100%
- Heart rate: 30 BPM to 240 BPM
- Perfusion: 0.2%, 2% and 10%
- Transmission: dark/thick, normal and light/thin
- Artifacts: respiration and ambient light
- Three editable test sequences
- R-curves: 8 including Masimo, Nellcor and Nonin
- Expandable pairing capabilities

FLUKE

🖌 ` RaySafe

VICTOREEN



Specifications

Physical specifications		
Display	2¼" x 1½" LCD display	
Size (WxDxH)	12.2 cm x 9.7 cm x 4.8 cm (4.8 in x 3.8 in x 1.9 in)	
Weight	8.8 oz.	
Electrical specifications		
Battery		
Туре	Rechargeable Lithium-Ion	
Charge time	Approximately two hours	
Operating duration	Approximately ten hours minimum	
AC adapter		
Input voltage	100 V ac to 240 V ac	
Input frequency	50/60 Hz	
Input current	0.5 A (rms)	
Output voltage	6 V dc	
Environmental specifications		
Operating temperature	0° C to 35° C (32° F to 95° F)	
Storage temperature	-35° C to 50° C (-31° F to 122° F)	
Operating humidity	20% to 80% RH (non-condensing)	
Measurements		
SpO ₂ saturation	70%, 75%, 80%, 85%, 90%, 95%, 97%, 98%, 99%, and 100%	
Heart Rate	30, 40, 60, 65, 80, 100, 120, 140, 150, 180 and 240 BPM	
Perfusion rate	0.2%, 2% and 10%	
Transmission level (finger)	Dark/thick, normal and light/thin	
Artifacts	Respiration or ambient light (50 Hz or 60 Hz)	





Ordering information

Models/descriptions

4111101	ProSim SPOT Light SPO2 Functional Tester, USA
4142735	ProSim SPOT Light SPO2 Functional Tester, Schuko
4142747	ProSim SPOT Light SPO2 Functional Tester, UK
4142758	ProSim SPOT Light SPO2 Functional Tester, Japan
4142764	ProSim SPOT Light SPO2 Functional Tester, Australia/China
4142814	ProSim SPOT Light SPO2 Functional Tester, Brazil

Standard accessories

4151274	ProSim SPOT Light Users Manual
4026823	ProSim SPOT Light Battery Pack
4026773	ProSim SPOT Light Power Supply Line Cord ProSim SPOT Light Line Cord (country-specific)
4180099	CCPS4 SPOT Light, PS4 SPOT Light Carry Case

Optional accessories

4199635	SPOT Light, 3 Year Gold Care Plan
4199647	SPOT Light, 1 Year Gold Care Plan
4199658	SPOT Light, 3 Year Silver Care Plan
4199664	SPOT Light, 1 Year Silver Care Plan
4199673	SPOT Light, 3 Year Bronze Care Plan
4199686	SPOT Light, 1 Year Bronze Care Plan
4034393	USB Cable
4026823	ProSim SPOT Light Battery Pack





About Fluke Biomedical

Fluke Biomedical is the world's leading manufacturer of quality biomedical test and simulation products. In addition, Fluke Biomedical provides the latest medical imaging and oncology quality-assurance solutions for regulatory compliance. Highly credentialed and equipped with a NVLAP Lab Code 200566-0 accredited laboratory, Fluke Biomedical also offers the best in quality and customer service for all your equipment calibration needs.

Today, biomedical personnel must meet the increasing regulatory pressures, higher guality standards, and rapid technological growth, while performing their work faster and more efficiently than ever. Fluke Biomedical provides a diverse range of software and hardware tools to meet today's challenges.

Fluke Biomedical regulatory commitment

As a medical test device manufacturer, we recognize and follow certain quality standards and certifications when developing our products. We are ISO 9001 and ISO 13485 medical device certified and our products are:

- CE Certified, where required
- NIST Traceable and Calibrated
- UL, CSA, ETL Certified, where required
- NRC Compliant, where required



绿测科技有限公司

广州总部:广州市番禺区陈边村金欧大道83号江潮创意园A栋208室 深圳分公司:深圳市龙华区龙华街道油松社区东环一路1号耀丰通工业园1-2栋2栋607 南宁分公司: 广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号 广州分公司:广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房 电话: 020-2204 2442 传真: 020-8067 2851 邮箱: Sales@greentest.com.cn 官网: www.greentest.com.cn



微信视频号

绿测工场服务号

LANDAUER[®]

🝋 RaySafe^{...}

